

# High-efficiency multideck Produce




MODEL		37203	HMAP 25203	18203
Unit type			Remote	
Temperature	°C		+5 to +12	
Power supply		230V AC; 50Hz; Single Phase		
Indoor design ambient		25°C; RH60%, Class 3		
Length <sup>1</sup>	mm	3750	2500	1875
Depth	mm	1100		
Height <sup>2</sup>	mm	2000		
Product loading volume	m <sup>3</sup>	9.75	6.5	4.88
Product display area	m <sup>2</sup>	2.86	1.91	1.43
End panel Standard		Glass end panel		
End panel optional		Mirror end panel		
Refrigerant		R22 / R404a		
Evaporator fans x power	Nos x W	3 x 36	2 x 36	
ESM fan optional	Nos x W	3 x 8.5	2 x 8.5	
Case controller standard		EKC102A		
Case controller optional		EKC202B		
Lights standard	Nos x W	18 x 36	12 x 36	12 x 30
Light specification	Type&Color	T8, Cool white		
LED optional	Nos x W	6 x 18	4 x 18	4 x 13
Shelves Quantity (450mm)	Nos	9	6	6
Shelves Quantity (500mm)	Nos	3	2	2
Specification		RoHS compliant, Power coated		
Anti sweat heater	Nos x W	Not provided		
Defrost heater in coil	W	Not provided		
Glass end panel heater	W	Not provided		
Contact for heaters		Not provided		
Color option		RAL7016 Anthracite grey, RAL7022 Umbra grey, RAL9003 Signal white, RAL9005 Jet black, RAL6018 Yellow green		
Internal external color		Unless specified internal & external color will be same		
Plastics & bumper color		Front, side bumper, glass trim - Gray color, PE round price trims & plastics - white color		

<sup>1</sup> - For each end panel depth 110mm to be added

<sup>2</sup> - Height of leg 50mm with level screw closed to be added



2.0m Height



Details provided are subject to change without notice due to continuous improvement.