

Slim multideck Meat / Dairy




MODEL	MSM80			MSD80			
	3720	2520	1820	3720	2520	1820	
Unit type	Remote						
Temperature	-1 to +8			+3 to +10			
Power supply	230V AC; 50Hz; Single Phase						
Indoor design ambient	25°C; RH60%, Class 3						
Length ¹	mm	3750	2500	1875	3750	2500	1875
Depth	mm	835					
Height ²	mm	2000					
Product loading volume	m ³	2.5	1.7	1.3	2.5	1.7	1.3
Product display area	m ²	9.7	6.5	5.3	9.7	6.5	5.3
End panel Standard	Glass end panel						
End panel optional	Mirror end panel						
Refrigerant	R22 / R404a						
Evaporator fans x power	Nos x W	5 x 60	3 x 60	3 x 60	5 x 60	3 x 60	3 x 60
Case controller standard	EKC102B						
Case controller optional	EKC202B						
Lights Quantity ³	Nos x W	3 x 36	2 x 36	2 x 30	15 x 36	10 x 36	10 x 30
Light specification	T8, Cool white						
LED optional	Nos x W	6 x 18	4 x 18	4 x 13	6 x 18	4 x 18	4 x 13
Shelves Quantity (350mm)	Nos	9	6	6	9	6	6
Shelves Quantity (450mm)	Nos	3	2	2	3	2	2
Specification	RoHS compliant, Power coated						
Anti sweat heater	Nos x W	Not provided					
Defrost heater in coil	W	1720	1080	850	1720	1080	850
Glass end panel heater	W					60	N/A
Contactor for heaters	Provided						
Color option	RAL7016 Anthracite grey, RAL7022 Umbra grey, RAL9003 Signal white, RAL9005 Jet black, RAL6018 Yellow green						
Internal external color	Unless specified internal & external color will be same						
Plastics & bumper color	Front, side bumper, glass trim - Gray color, PE round ,price trims & plastics - white color						

¹ - For each end panel depth 50mm to be added

² - Height of leg 50mm with level screw closed to be added

³ - Extra lights can be provided for Meat case on request



Details provided are subject to change without notice due to continuous improvement.

R-0.0, 1 Oct12